

1. Identification

Product identifier HyPrene 60

Other means of identification
CAS number 64742-53-6

Recommended use Tire Oils, Rubber Compounding, Automotive & Industrial Hoses, Dedusting, Plasticizer, Titanium Dioxide Wash, Compressor Wash Oils, Hydraulic Fracturing Oil, Adhesives, Carpet Backing, Feed Stock for White Oil, Refrigeration Oil, Diluents and Carriers, Carbon Black, Banbury Dust Stop, Defoamers, Sealants, Belts & Hoses, Coatings, Leather Tanning, Agriculture Oils.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company: Ergon, Inc.

Address: P.O. Box 1639
 Jackson, MS 39215

E-mail: sds@ergon.com

Emergency Contacts

Customer Service: 1-800-222-7122

Chemtrec: 1-800-424-9300 After Business Hours (North America Only)
 1-703-527-3887 After Business Hours (International)

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Not classified.

Health hazards Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Not assigned.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS No./Unique ID	%
Distillates (petroleum), hydrotreated light naphthenic		64742-53-6	≤100

Composition comments	Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.
-----------------------------	--

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted. NFPA 30 Class: Combustible Liquid Class IIIB

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). The product is immiscible with water and will spread on the water surface. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. The product is insoluble in water.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
--------------------------------------	---

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Additional components	Type	Value	Form
Oil mist, mineral	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values (TLV)

Additional components	Type	Value	Form
Oil mist, mineral	TWA	5 mg/m3	Inhalable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Additional components	Type	Value
Oil mist, mineral	IDLH	2500 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Additional components	Type	Value	Form
Oil mist, mineral	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Color	Colorless to slight yellow tint
Odor	Mild Petroleum Odor
Melting point/freezing point	-81.4 °F (-63 °C) ASTM D5950/ISO 3016
Boiling point or initial boiling point and boiling range	543.2 °F (284 °C) ASTM D86/ ISO 3294
Flammability	Will burn if involved in a fire.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not determined.

Explosive limit - upper (%) Not determined.

Flash point 311.0 °F (155.0 °C) Cleveland Open Cup ASTM D92/ ISO 2592

Auto-ignition temperature >600 °F (>315.56 °C) ASTM E659

Decomposition temperature	Not determined.
pH	Not applicable.
Kinematic viscosity	9.6 cSt ASTM D445 (104 °F (40 °C))
Solubility	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water)	Not applicable.
Vapor pressure	<0.1 hPa (68 °F (20 °C))
Density and/or relative density	
Relative density	0.885 (60.08 °F (15.6 °C) ASTM D4052/ ISO 12185)
Vapor density	>5
Particle characteristics	
Particle size	Not applicable, material is a liquid.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Defatting of the skin. Aspiration may cause pulmonary edema and pneumonitis.
---	--

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
<i>Aerosol</i>		
LC50	Rat	> 5.53 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation. May cause defatting of the skin, but is neither an irritant nor a sensitizer.
----------------------------------	--

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
--	--

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Highly refined mineral oil (CAS -) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability Expected to be inherently biodegradable.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects Oil spills are generally hazardous to the environment.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to IMO instruments Not established.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
This SDS complies with the OSHA Hazard Communication Standard (29 CFR § 1910.1200), as amended in the final rule published May 20, 2024.

Toxic Substances Control Act (TSCA)

This substance is on the TSCA 8(b) inventory and is designated "active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).		

16. Other information, including date of preparation or last revision

Issue date	01-05-2026
Version #	01
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Disclaimer	Ergon Refining, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.