# ERGON E

# **SAFETY DATA SHEET**

#### 1. Identification

Product identifier Other means of identification	HyGold P600N None.
Recommended use	Metalworking Fluids, Industrial Lubricants, Grease Manufacturing, Hydraulic Oils, Gear Oils, Heavy Duty Engine Oil, Bar & Chain, Carriers & Diluents, Engine Oil.
<b>Recommended restrictions</b>	None known.
Manufacturer/Importer/Suppl	ier/Distributor information
Company:	Ergon, Inc.
Address:	P.O. Box 1639
	Jackson, MS 39215
E-mail:	sds@ergon.com
Emergency Contacts	
Customer Service:	1-800-222-7122
Chemtrec:	1-800-424-9300 After Business Hours (North America Only)
	1-703-527-3887 After Business Hours (International)

#### 2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	Not applicable.
Hazard statement	Not applicable.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC		64742-65-0	60 - 70
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED		64742-62-7	30 - 40

#### 4. First-aid measures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.
Skin contact	Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact	Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion	Call a poison control center immediately. Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Most important symptoms/effects, acute and delayed	Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Contact physician if discomfort continues.
5. Fire-fighting measures	S
Suitable extinguishing media	Water spray or fog. Foam. Do not use water jet as an extinguisher, as this will spread the fire. Dry chemicals. Carbon dioxide (CO2). Halon.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Cool containers exposed to flames with water until well after the fire is out. Use pressurized air mask if product is involved in a fire.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. The product is immiscible with water and will spread on the water surface. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
	Never return spills in original containers for re-use.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.
7. Handling and storage	
Precautions for safe handling	All handling to take place in well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Remove and wash contaminated clothing promptly. Shower after work.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Pern Material	Туре	Value	Form
HyGold P600N	PEL	5 mg/m3	Mist.
Components	Туре	Value	Form
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	PEL ,	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Lin	nit Values (TLV)		
Material	Туре	Value	Form
HyGold P600N	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS 64742-62-7)	TWA	5 mg/m3	Inhalable fraction.
NIOSH. Immediately Dar Components	ngerous to Life or Health (IDLH) Va Type	llues, as amended Value	
DISTILLATES		-	
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	e to Chemical Hazards Recommend	ed Exposure Limits (REL) Value	Form
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material	e to Chemical Hazards Recommend Type	Value	Form
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) <b>US. NIOSH: Pocket Guide</b>	e to Chemical Hazards Recommend Type Ceiling	Value       1800 mg/m3	
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N	e to Chemical Hazards Recommend Type Ceiling STEL	Value       1800 mg/m3       10 mg/m3	Mist.
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components	e to Chemical Hazards Recommend Type Ceiling STEL Type	Value 1800 mg/m3 10 mg/m3 Value	
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling	Value       1800 mg/m3       10 mg/m3       Value       1800 mg/m3	Mist.
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling	Value 1800 mg/m3 10 mg/m3 Value	Mist.
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling	Value       1800 mg/m3       10 mg/m3       Value       1800 mg/m3       10 mg/m3	Mist. <b>Form</b>
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0)	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling Ceiling	Value     1800 mg/m3     10 mg/m3     Value     1800 mg/m3     10 mg/m3     for the ingredient(s).     ing appropriate local extraction,     acceeded. Adequate ventilation sh	Mist. Form Mist. to ensure that the defined
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) logical limit values propriate engineering trols	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling , STEL No biological exposure limits noted f Provide adequate ventilation, includi occupational exposure limit is not ex	Value     1800 mg/m3     10 mg/m3     Value     1800 mg/m3     10 mg/m3     for the ingredient(s).     ing appropriate local extraction,     xceeded. Adequate ventilation sh     rated.     uipment	Mist. Form Mist. to ensure that the defined
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) logical limit values propriate engineering trols	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling Ceiling , STEL No biological exposure limits noted f Provide adequate ventilation, includi occupational exposure limit is not ex material is heated or mists are gene res, such as personal protective equ	Value     1800 mg/m3     10 mg/m3     Value     1800 mg/m3     10 mg/m3     for the ingredient(s).     ing appropriate local extraction,     xceeded. Adequate ventilation sh     rated.     uipment	Mist. Form Mist. to ensure that the defined
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) logical limit values propriate engineering trols ividual protection measure Eye/face protection	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling Ceiling , STEL No biological exposure limits noted f Provide adequate ventilation, includi occupational exposure limit is not ex material is heated or mists are gene res, such as personal protective equ	Value   1800 mg/m3   10 mg/m3   Value   1800 mg/m3   10 mg/m3   for the ingredient(s).   ing appropriate local extraction, sceeded. Adequate ventilation shrated.   uipment   ed.	Mist. Form Mist. to ensure that the defined hould be provided whenever
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) logical limit values propriate engineering trols ividual protection measure Eye/face protection Skin protection	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling Ceiling , STEL No biological exposure limits noted f Provide adequate ventilation, includi occupational exposure limit is not ex material is heated or mists are gene res, such as personal protective equ Goggles/face shield are recommende Chemical resistant gloves are recom	Value     1800 mg/m3     10 mg/m3     Value     1800 mg/m3     10 mg/m3     for the ingredient(s).     ing appropriate local extraction,     cceeded. Adequate ventilation sh     rated.     uipment     ed.     mended. If contact with forearm	Mist. Form Mist. to ensure that the defined hould be provided whenever
(PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) US. NIOSH: Pocket Guide Material HyGold P600N Components DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) logical limit values propriate engineering trols ividual protection measure Eye/face protection Skin protection Hand protection	e to Chemical Hazards Recommend Type Ceiling STEL Type Ceiling Ceiling , STEL No biological exposure limits noted f Provide adequate ventilation, includi occupational exposure limit is not ex material is heated or mists are gene res, such as personal protective equations Goggles/face shield are recommended Chemical resistant gloves are recom	Value     1800 mg/m3     10 mg/m3     Value     1800 mg/m3     10 mg/m3     for the ingredient(s).     ing appropriate local extraction,     acceeded. Adequate ventilation shrated.     uipment     ed.     mended. If contact with forearm     ommended. Launder contaminaries not normally required. In case	Mist. Form Mist. to ensure that the defined hould be provided whenever

General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
considerations	before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants.

#### 9. Physical and chemical properties

pri ingolear ana enemicar	
Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Color	Amber
Odor	Hydrocarbon-like.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	7.2 °F (-13.78 °C) ASTM D5949/ ISO 3016
Initial boiling point and boiling range	> 740 - < 1100 °F (> 393.33 - < 593.33 °C) ASTM D2887/ ISO 3294
Flash point	520.0 °F (271.1 °C) Cleveland Open Cup ASTM D92/ ISO 2592
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or e	xplosive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.87 (60 °F (15.56 °C) ASTM D4052/ ISO 12185)
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	>600 °F (>315.56 °C) ASTM E659
Decomposition temperature	Not available.
Viscosity	114.5 cSt (104 °F (40 °C) ASTM D445/ ISO 3104)
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
10. Stability and reactivit	-
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
11. Toxicological informa	ation

## **11.** Toxicological information

#### Information on likely routes of exposure

Inhalation	May be harmful if inhaled. However, this product does not currently meet the criteria for classification.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	May be irritating to eyes.
Ingestion	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.

incompatible

Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.	
Information on toxicological effects		
Acute toxicity	Not classified.	
Skin corrosion/irritation	May cause defatting of the skin, but is neither an irritant nor a sensitizer. Not classified.	
Serious eye damage/eye irritation	Not classified.	
Respiratory or skin sensitization	on	
Respiratory sensitization	Not classified.	
Skin sensitization	Not classified.	
Germ cell mutagenicity	Non-mutagenic based on Modified Ames Assay.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	l Evaluation of Carcinogenicity	
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED 3 Not classifiable as to carcinogenicity to humans. (CAS 64742-62-7)		
OSHA Specifically Regulat	ed Substances (29 CFR 1910.1001-1053)	
Not listed.		
US. National Toxicology Pi Not listed.	rogram (NTP) Report on Carcinogens	
Reproductive toxicity	Contains no ingredient listed as toxic to reproduction.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not classified.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged or repeated contact may cause drying, cracking, or irritation of the skin.	
12. Ecological information	on	

# EcotoxicityNot expected to be harmful to aquatic organisms.Persistence and degradabilityNot inherently biodegradable.Bioaccumulative potentialBioaccumulation is unlikely to be significant because of the low water solubility of this product.Mobility in soilNo data available.Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Disposal instructions	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Not applicable.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.

#### 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### Not regulated as dangerous goods. Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code General information Not regulated as dangerous goods. 15. Regulatory information **US** federal regulations All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. CERCLA/SARA Hazardous Substances - Not applicable. All components of the mixture on the TSCA 8(b) inventory are designated **Toxic Substances Control Act** "active". (TSCA) TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) SARA 302 Extremely hazardous substance Not listed. SARA 311/312 No Hazardous chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) US state regulations US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a)) DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (CAS 64742-65-0) RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED (CAS 64742-62-7) **California Proposition 65** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov. **International Inventories** Country(s) or region On inventory (yes/no)\* **Inventory name** Australia Australian Inventory of Industrial Chemicals (AICIS) Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Substances Yes Europe (EINECS)

European List of Notified Chemical Substances (ELINCS)

Inventory of Existing and New Chemical Substances (ENCS)

Europe

Japan

IMDG

No

Yes

Country(s) or region	Inventory name On inventory (yes	5/no)*
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information, including date of preparation or last revision

- · · · · · · · · · · · · · · · · · · ·	
Issue date	01-16-2015
Revision date	06-14-2024
Version #	04
Further information	Local CHEMTREC Numbers: CHEMTREC Mexico: 1-800-681-9531
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
References	ACGIH ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices EPA: AQUIRE database IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics ILO Safety Cards International Labour Organization International Maritime Organization Marine Pollutants List NFPA Hazardous Chemical Data Sheets NIOSH Pocket Guide Registry of Toxic Effects of Chemical Substances (RTECS) US DOT Hazardous Materials Regulations
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Refining, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.