SAFETY DATA SHEET

Ergon-West Virginia, Inc.

1. Identification

Product identifier Unleaded Premium 93 Gasoline with 10% Ethanol

Other means of identificationNot available.Recommended useNot available.Recommended restrictionsNone known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer:Ergon - West Virginia, Inc.Address:9995 Ohio River Blvd.Newell, WV 26050

E-mail: sds@ergon.com

Emergency Contacts

Ergon - West Virginia, 1-304-387-4343 Normal Business Hours

Inc.:

Chemtrec: 1-800-424-9300 After Business Hours (North America Only)

1-703-527-3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 1Health hazardsAcute toxicity, oralCategory 3Acute toxicity, inhalationCategory 4CarcinogenicityCategory 1A

Reproductive toxicity (fertility, the unborn child)

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Not available.

Hazard statement Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May be

fatal if swallowed and enters airways. Harmful if inhaled. Extremely flammable liquid and vapor.

Category 2

May cause cancer. Toxic if swallowed.

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or

vapor. Do not eat, drink or smoke when using this product. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Keep container tightly closed.

Response In case of fire: Use CO2 for extinction. Wash hands after handling. Specific treatment see Section

4 of this SDS. IF exposed or concerned: Get medical advice/attention. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Remove/Take off

immediately all contaminated clothing. Rinse skin with water/shower. IF SWALLOWED:

Immediately call a POISON CENTER or doctor/physician.

Storage Store away from incompatible materials. Store locked up. Store in a well-ventilated place. Keep

cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

See section 13 of this SDS for disposal instructions.

Material name: Unleaded Premium 93 Gasoline with 10% Ethanol

5703 Version #: 01 Issue date: 05-22-2015

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
GASOLINE		86290-81-5	< 93
ETHANOL		64-17-5	5 - 10
BENZENE, DIMETHYL		1330-20-7	1 - 10
BENZENE, METHYL-		108-88-3	1 - 10
HEXANE		110-54-3	< 5
BENZENE		71-43-2	< 2
ETHYLBENZENE		100-41-4	< 2
NAPHTHALENE		91-20-3	< 1

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Remove and isolate contaminated clothing and shoes. Get medical

attention if irritation develops and persists. Wash clothing separately before reuse. For minor skin

contact, avoid spreading material on unaffected skin.

Eye contact Get medical attention if irritation develops and persists. Immediately flush eyes with plenty of water

for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove

the lens. Remove contact lenses, if present and easy to do. Continue rinsing.

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid

of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce

vomiting without advice from poison control center.

Direct contact with eyes may cause temporary irritation.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

readment needed

Persons with pre-existing respiratory tract, skin, lung (such as asthma), and kidney disorders may be aggravated by exposure to this product. Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances

enhances these effects.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Water Spray or Fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment

and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire-fighting Move containers from fire

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions.

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Material name: Unleaded Premium 93 Gasoline with 10% Ethanol

5703 Version #: 01 Issue date: 05-22-2015 2 / 12

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling Conditions for safe storage, including any incompatibilities

Avoid prolonged exposure. Observe good industrial hygiene practices.

Store in original tightly closed container. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Occupational exposure limits

Components	Туре	Value
BENZENE (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm
US. OSHA Table Z-1 Limits for A	ir Contaminants (29 CFR 1	.910.1000)
Components	Туре	Value
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m3
,		100 ppm
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m3
,		1000 ppm
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m3
		100 ppm
HEXANE (CAS 110-54-3)	PEL	1800 mg/m3
		500 ppm
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m3
,		10 ppm
US. OSHA Table Z-2 (29 CFR 191	-	
Components	Туре	Value
BENZENE (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
BENZENE, METHYL- (CAS 108-88-3)	Ceiling	300 ppm
•	TWA	200 ppm
US. ACGIH Threshold Limit Valu	es	
Components	Туре	Value
BENZENE (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
BENZENE, DIMETHYL (CAS 1330-20-7)	STEL	150 ppm
,	TWA	100 ppm
BENZENE, METHYL- (CAS 108-88-3)	TWA	20 ppm
ETHANOL (CAS 64-17-5)	STEL	1000 ppm
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm
GASOLINE (CAS 86290-81-5)	STEL	500 ppm
	TWA	300 ppm
HEXANE (CAS 110-54-3)	TWA	50 ppm
NAPHTHALENE (CAS	TWA	10 ppm
91-20-3)		

Material name: Unleaded Premium 93 Gasoline with 10% Ethanol

5703 Version #: 01 Issue date: 05-22-2015

US. NIOSH: Pocket Guide to Ch Components	emical Hazards Type	Value	
BENZENE (CAS 71-43-2)	STEL	1 ppm	
	TWA	0.1 ppm	
BENZENE, METHYL- (CAS 108-88-3)	STEL	560 mg/m3	
-		150 ppm	
	TWA	375 mg/m3	
		100 ppm	
ETHANOL (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3	
,		125 ppm	
	TWA	435 mg/m3	
		100 ppm	
HEXANE (CAS 110-54-3)	TWA	180 mg/m3	
,		50 ppm	
NAPHTHALENE (CAS 91-20-3)	STEL	75 mg/m3	
-		15 ppm	
	TWA	50 mg/m3	
		10 ppm	

Biological limit values

ACGIH Biological Exposu Components	ıre Indices Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 μg/g	S-Phenylmerca pturic acid	Creatinine in urine	*
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, METHYL- (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
HEXANE (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedion , without hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BENZENE (CAS 71-43-2)
BENZENE, METHYL- (CAS 108-88-3)
HEXANE (CAS 110-54-3)

US - Minnesota Haz Subs: Skin designation applies
BENZENE, METHYL- (CAS 108-88-3)

US ACGIH Threshold Limit Values: Skin designation

Can be absorbed through the skin.

Can be absorbed through the skin.

Skin designation applies.

BENZENE (CAS 71-43-2)

Can be absorbed through the skin.

HEXANE (CAS 110-54-3)

Can be absorbed through the skin.

NAPHTHALENE (CAS 91-20-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Light orange. Odor Characteristic. **Odor threshold** Not available. Not available. рH

-173.38 °F (-114.1 °C) estimated Melting point/freezing point

Initial boiling point and

boiling range

85 °F (29.44 °C) IBP

Flash point -45.0 °F (-42.8 °C) **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 1.1 % estimated

(%)

Flammability limit -

upper (%)

8 % estimated

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available. **Relative density** < 0.8

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

437 °F (225 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. **Viscosity**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents. Halogens. **Hazardous decomposition** No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Ingestion Expected to be a low ingestion hazard. **Inhalation** Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. **Eve contact** Direct contact with eyes may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

oduct	Species	Test Results
leaded Premium 93 Gasc	line with 10% Ethanol (CAS Mixture)	
Acute		
<i>Dermal</i>	Dalahit.	1500 CCCC million actions to d
LD50	Rabbit	1566.6666 ml/kg estimated
		577.1815 g/kg estimated
	Rat	6666.667 g/kg estimated
<i>Inhalation</i> LC50	Mouse	44444 4452 mmm 24 House actionated
LC30	Mouse	44444.4453 ppm, 24 Hours estimated 588.9904 mg/l, 4 Hours estimated
LD	Mouse	- .
LD	Mouse	34851.3398 mg/l, 5 Minutes estimated
<i>Oral</i> LD50	Dog	83.0628 g/kg estimated
LD30	Guinea pig	84.573 g/kg estimated
	Mouse	32136.3809 mg/kg estimated
	Rat	
		1095.5282 mg/kg estimated
Othor	Wistar rat	2450 mg/kg estimated
<i>Other</i> LD50	Mouse	2999.4631 mg/kg estimated
LD30	riouse	10.5716 ml/kg estimated
	Rat	84.3951 mg/kg estimated
omponents	Species Species	Test Results
NZENE (CAS 71-43-2)	Species	lest results
Acute		
Inhalation		
LC50	Mouse	9980 ppm
	Rat	10000 ppm, 7 Hours
Oral		
LD50	Mouse	4700 mg/kg
	Rat	3306 mg/kg
Other		
LD50	Mouse	340 mg/kg
		0.28 ml/kg
	Rat	2.89 mg/kg
NZENE, DIMETHYL (CAS	1330-20-7)	
Acute		
<i>Dermal</i>	Rabbit	12 alla
LD50	Rabbit	> 43 g/kg
<i>Inhalation</i> LC50	Mouse	3907 mg/l, 6 Hours
2030	Rat	6350 mg/l, 4 Hours
Oral	Nat	0330 Hig/I, T Hours
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
Other	Nac	3323 0000 Hig/kg
LD50	Rat	3.8 mg/kg
	· · · · · ·	טיי ונייי די ד

Components Species Test Results BENZENE, METHYL- (CAS 108-88-3) **Acute** Dermal LD50 Rabbit 12124 mg/kg 14.1 ml/kg Inhalation LC50 5320 ppm, 8 Hours Mouse 400 ppm, 24 Hours Rat 26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours Oral LD50 2.6 g/kg Rat Other LD50 Mouse 59 mg/kg 1332 mg/kg Rat ETHANOL (CAS 64-17-5) **Acute** Inhalation LC50 Mouse 39 mg/l, 4 Hours Rat 20000 ppm, 10 Hours Oral LD50 Dog 5.5 g/kg Guinea pig 5.6 g/kg Mouse 3450 mg/kg Rat 6.2 g/kg Other LD50 Mouse 933 mg/kg Rat 1440 mg/kg ETHYLBENZENE (CAS 100-41-4) **Acute** Dermal LD50 Rabbit 17800 mg/kg Oral LD50 Rat 3500 mg/kg Other LD50 Mouse 2272 mg/kg HEXANE (CAS 110-54-3) **Acute** Inhalation LC50 Mouse 48000 ppm, 4 Hours Oral Rat LD50 24 mg/kg Wistar rat 49 mg/kg NAPHTHALENE (CAS 91-20-3) **Acute** Dermal LD50 Rabbit > 2 g/kg Rat > 20 g/kg Oral LD50 Guinea pig 1200 mg/kg

Components	Species	Test Results
	Rat	490 mg/kg
Other		
LD50	Mouse	100 mg/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE (CAS 71-43-2) 1 Carcinogenic to humans.

BENZENE, DIMETHYL (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

BENZENE, METHYL- (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

ETHYLBENZENE (CAS 100-41-4)

GASOLINE (CAS 86290-81-5)

NAPHTHALENE (CAS 91-20-3)

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2) Known To Be Human Carcinogen.

NAPHTHALENE (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2) Cancer

Reproductive toxicityComponents in this product have been shown to cause birth defects and reproductive disorders in

laboratory animals.

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
Unleaded Premium 93 (Gasoline with 10%	Ethanol (CAS Mixture)	
Crustacea	EC50	Daphnia	248.3968 mg/l, 48 hours estimated
Fish	LC50	Fish	814.9794 mg/l, 96 hours estimated
Components		Species	Test Results
BENZENE (CAS 71-43-2)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours
BENZENE, DIMETHYL (CAS 1330-20-7)		
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours
BENZENE, METHYL- (CA	AS 108-88-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

Material name: Unleaded Premium 93 Gasoline with 10% Ethanol

5703 Version #: 01 Issue date: 05-22-2015 8 / 1

Components Species Test Results ETHANOL (CAS 64-17-5) **Aquatic** EC50 Water flea (Daphnia magna) 7.7 - 11.2 mg/l, 48 hours Crustacea Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours ETHYLBENZENE (CAS 100-41-4) **Aquatic** Crustacea EC50 Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours HEXANE (CAS 110-54-3) **Aquatic** Fish LC50 Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours NAPHTHALENE (CAS 91-20-3) **Aquatic** Crustacea EC50 Water flea (Daphnia magna) 1.09 - 3.4 mg/l, 48 hours

LC50

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZENE	2.13
BENZENE, DIMETHYL	3.12 - 3.2
BENZENE, METHYL-	2.73
ETHANOL	-0.31
ETHYLBENZENE	3.15
HEXANE	3.9
NAPHTHALENE	3.3

Mobility in soil No data available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Pink salmon (Oncorhynchus gorbuscha) 1.11 - 1.68 mg/l, 96 hours

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Fish

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1203

UN proper shipping name Gasoline includes gasoline mixed with ethyl alcohol, with not more than 10 percent alcohol

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group II

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Special provisions 144, 177, B1, B33, IB2, T4, TP1

Packaging exceptions 150
Packaging non bulk 202
Packaging bulk 242

^{*} Estimates for product may be based on additional component data not shown.

IATA

UN1203 **UN** number **UN** proper shipping name Petrol Transport hazard class(es)

Class 3 Subsidiary risk **Packing group** ΙΙ **Environmental hazards** No. **ERG Code** 3H

Special precautions for

user

Read safety instructions, SDS and emergency procedures before handling.

Other information Passenger and cargo

Allowed.

aircraft

Allowed. Cargo aircraft only

IMDG

UN number UN1203

MOTOR SPIRIT or GASOLINE or PETROL **UN proper shipping name**

Transport hazard class(es) Class **Subsidiary risk Packing group** ΙΙ **Environmental hazards**

Marine pollutant No. F-E, S-E

Special precautions for Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2) Listed. BENZENE, DIMETHYL (CAS 1330-20-7) Listed. BENZENE, METHYL- (CAS 108-88-3) Listed. ETHANOL (CAS 64-17-5) Listed. ETHYLBENZENE (CAS 100-41-4) Listed. GASOLINE (CAS 86290-81-5) Listed.

HEXANE (CAS 110-54-3) Listed. NAPHTHALENE (CAS 91-20-3) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)

Cancer

Central nervous system

Blood Aspiration Skin Eye

respiratory tract irritation

Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BENZENE, DIMETHYL	1330-20-7	1 - 10	
HEXANE	110-54-3	< 5	
BENZENE	71-43-2	< 2	
ETHYLBENZENE	100-41-4	< 2	
NAPHTHALENE	91-20-3	< 1	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)

BENZENE, DIMETHYL (CAS 1330-20-7) BENZENE, METHYL- (CAS 108-88-3) ETHYLBENZENE (CAS 100-41-4) HEXANE (CAS 110-54-3)

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2)

BENZENE, METHYL- (CAS 108-88-3)

DEA Essential Chemical Code Number

BENZENE, METHYL- (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

BENZENE, METHYL- (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

BENZENE, METHYL- (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

BENZENE (CAS 71-43-2)

ETHANOL (CAS 64-17-5)

BENZENE, DIMETHYL (CAS 1330-20-7) BENZENE, METHYL- (CAS 108-88-3)

ETHYLBENZENE (CAS 100-41-4) HEXANE (CAS 110-54-3) NAPHTHALENE (CAS 91-20-3)

US. New Jersey Worker and Community Right-to-Know Act

BENZENE (CAS 71-43-2) 500 LBS
BENZENE, DIMETHYL (CAS 1330-20-7) 500 LBS
BENZENE, METHYL- (CAS 108-88-3) 500 LBS
ETHYLBENZENE (CAS 100-41-4) 500 LBS

HEXANE (CAS 110-54-3) 500 LBS NAPHTHALENE (CAS 91-20-3) 500 LBS

US. Pennsylvania RTK - Hazardous Substances

BENZENE (CAS 71-43-2)

BENZENE, DIMETHYL (CAS 1330-20-7) BENZENE, METHYL- (CAS 108-88-3)

ETHANOL (CAS 64-17-5) ETHYLBENZENE (CAS 100-41-4) GASOLINE (CAS 86290-81-5) HEXANE (CAS 110-54-3) NAPHTHALENE (CAS 91-20-3)

US. Rhode Island RTK

BENZENE (CAS 71-43-2)

BENZENE, DIMETHYL (CAS 1330-20-7) BENZENE, METHYL- (CAS 108-88-3) ETHYLBENZENE (CAS 100-41-4) HEXANE (CAS 110-54-3) NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)
ETHANOL (CAS 64-17-5)
Listed: April 29, 2011
Listed: July 1, 1988
ETHYLBENZENE (CAS 100-41-4)
NAPHTHALENE (CAS 91-20-3)
Listed: April 19, 2002
US - California Proposition 65 - CRT: Listed date/Developmental toxin
BENZENE (CAS 71-43-2)
Listed: December 26, 1997

BENZENE, METHYL- (CAS 108-88-3) Listed: January 1, 1991 ETHANOL (CAS 64-17-5) Listed: October 1, 1987 US - California Proposition 65 - CRT: Listed date/Female reproductive toxin BENZENE, METHYL- (CAS 108-88-3) Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Inventory name

BENZENE (CAS 71-43-2) Listed: December 26, 1997

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 05-22-2015

Version # 01

United States & Puerto Rico

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Material name: Unleaded Premium 93 Gasoline with 10% Ethanol

5703 Version #: 01 Issue date: 05-22-2015

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).