

1. Identification

Product identifier	Shingle Coating Blend
Other means of identification	
Product Code	1860
Recommended use	Not available.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer:	Tricor Refining, LLC.
Address:	P.O. Box 5877 Bakersfield, CA 93388
24-hour Telephone Number:	(661) 393-7110
CHEMTREC:	1-800-424-9300 (North America) 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements

Signal word	Warning
Hazard statement	Suspected of causing cancer.
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF exposed or concerned: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC)	Heated product will cause thermal burns. See section 11 of the SDS for additional information on health hazards.
Supplemental information	None.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	100

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY. Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of the asphalt due to the risk of adhesion. Get immediate medical attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention or advice.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed Potential for severe thermal burns.

5. Fire-fighting measures

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical Irritating and toxic gases or fumes may be released during a fire.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may cause frothing.

Specific methods In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up Dike far ahead of spill for later disposal. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal.

7. Handling and storage

Precautions for safe handling Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Conditions for safe storage, including any incompatibilities Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - NIOSH Components	Type	Value
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses. Wear face shield if there is risk of splashes.

Hand protection Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended. Wear 100% cotton clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards During product use, there is a risk of thermal burns.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Solid.

Physical state	Solid.
Form	Solid.
Color	Dark brown to. Black
Odor	Hydrocarbon-like.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 650 °F (> 343.33 °C)
Flash point	> 450.0 °F (> 232.2 °C) Cleveland Open Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	650 °F (343.33 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal temperature conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Do not overheat product.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.
Inhalation	May be harmful if inhaled. However, this product does not currently meet the criteria for classification.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	May be irritating to eyes.
Symptoms related to the physical, chemical and toxicological characteristics	Not available.

Information on toxicological effects

Acute toxicity	Not classified.
Skin corrosion/irritation	Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye irritation	Not classified.
Respiratory or skin sensitization	
Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	Non-mutagenic based on Modified Ames Assay.
Carcinogenicity	Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Contains no ingredient listed as toxic to reproduction
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	Prolonged or repeated contact may cause drying, cracking, or irritation of the skin.

12. Ecological information

Ecotoxicity	This product has no known eco-toxicological effects.
Persistence and degradability	Not available.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Other adverse effects	Not available.

13. Disposal considerations

Disposal instructions	Allow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.
Hazardous waste code	Not applicable.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	No special precautions.

14. Transport information

DOT

UN number	UN3257
UN proper shipping name	Elevated temperature liquid, n.o.s. (ASPHALT)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Special precautions for user	Not available.

IATA

UN number	Not available.
UN proper shipping name	Forbidden
Transport hazard class(es)	
Class	Forbidden
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Forbidden.
Cargo aircraft only	Forbidden.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT**Further information**

Shipping Marking: HOT. Transport by air is forbidden when shipped above 212°F (100°C).

15. Regulatory information**US federal regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

No

Hazardous chemical**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-15-2015

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.